

### INB713Z-RTN

### 2 Megapixel Premium Series IP IR Bullet Camera

Infinique offers a wide range of IP based high definition cameras available in various housing formats, including Box, Dome and Bullet. Our cameras are equipped with superior image sensor and digital signal processor to produce sharp, crisp pictures and are enclosed in weather and vandal resistant housings making it suitable for use in all security applications. The ONVIF compliance of the cameras helps in easy integration, providing peace of mind for your investment. From small to very large installations, Infinique's cameras are reliable, future proof and an ideal solution for your video surveillance needs.

The INB713Z-RTN is a 2 Megapixel high resolution IR Camera with Motorized Zoom. It is built with a vandal resistant aluminum housing, incorporating a [high quality image sensor and IR LEDs to provide clear crisp images both during the Day and Night.

The camera comes equipped with a 2.8~12mm motorized lens with remote zoom and focus for easy setup of field of view. The Auto Iris control allows the camera to automatically set its iris position to maximize image quality in all lighting conditions. The camera streams real-time video at high definition resolution using H.264 or H.265 compression optimizing the bandwidth and increasing storage efficiency.


Built-in PoE for powering the camera and the flexible 3-axis bracket for fixing it on ceiling or wall, provides the convenience for installers to complete the installation quickly and with ease. These excellent IP cameras are highly suitable for video surveillance of government buildings, residential apartments, schools, colleges, universities, shopping malls, hospitals, hotels, industrial parks, and corporate offices.

### **Product Features**

- 1/2.8" Progressive Sensor
- 2 Megapixel Resolution
- Up to 30fps at 1920 x 1080
- IR Distance 45 meters
- 2.8~12mm Motorized Zoom Lens
- Diaital WDR
- H.265, H.264 and MJPEG Compressions
- Up to 3 Simultaneous Video Streams
- S/N Ratio of more than 50dB
- Micro SD Card Slot for Onboard Storage
- Composite Video Output
- Two Way Audio, Alarm I/O
- Power Over Ethernet (PoE), IEEE 802,3af
- IP67, IK07 Rated
- Vandal Proof Aluminum Alloy Housing
- Wall or Ceiling Mount with 3 Axis Bracket
- ONVIF Compliant




#### **Dimensions**



#### **Accessories**







Part Number: IJBBCM-134 Ceiling Mount Junction Box



Part No: IBKTCM Pendant Ceiling Bracket



Part No: IBBCPM Pole Mount Bracket



Part No: IBCRWM Corner Mount Bracket

# INB713Z-RTN





IMAGE PERFORMANCE		
Image Sensor	1/2.8" Progressive Sensor	
Effective Pixels (H x V)	1920 × 1080	
Resolution (Megapixels)	2	
Minimum Illumination	0.002 lux (AGC ON) 0 lux with IR ON	
Image Rate (FPS)	30	
S/N Ratio	More than 50dB	
IR Distance	45	
LENS		
Focal Length (mm)	2.8~12 Motorized Zoom Lens	
Iris	DC Auto Iris, Manual	
Aperture Ratio	F1.2	
Angle of View (deg)	H:107 (Wide)~35 (Tele), V:54 (Wide)~20 (Tele)	
VIDEO AND AUDIO		
Video Compression	H.265 Main Profile H.264 Baseline Profile/Main Profile/High Profile	
Main Stream	1920x1080, 1280x960, 1280x720	
Sub Stream	1280x720, 640x480, 320x240	
Mobile Stream	640x480, 320x240	
Electronic Shutter Control	1/5 ~ 1/20,000 sec	
Day/Night Control	True Day/Night with IR Cut Filter	
Flicker Control	50 Hz, 60 Hz	
WDR	Digital WDR	
3D Noise Reduction	Auto / Manual / Disable	
White Balance	Automatic / Manual	
Back Light Compensation	On / Off	
Automatic Gain Control	Auto/Manual, Adjustable Level	
Privacy Mask Zones	Up to 4 Privacy Mask Zones	
Audio Compression	G.711A/ G.711U/ G.726	
Audio Input/ Output	Line level input and output, 3.5mm A/V Interface	
Video Output	2 pin terminal block	
Video Bit rate	256K-8M ,Supports CBR/VBR	
OSD	Camera ID, Timestamp	
Image Orientation	Image Flip, Corridor Mode, Rotation	
Image Controls	Brightness, Contrast, Hue, Saturation, Sharpness	
Advanced Functions	Image Rotation, Gain Control, Anti-Fog, Anti-False Color, Anti-Shake, IR Detection	
VIDEO ANALYTICS		
Motion Detection	Multiple Zones	
Advance Video Analytics	Tamper, Out Of Focus, Sound, Perimeter Intrusion, Line Crossing, Stationary Object, Pedestrian Detection, People Counting, Face Detection	

LOCAL STORAGE	
Storage Type	Micro SD card, Max up to 128GB
Recording	Video and Image; Auto / Schedule/ Manual / On Event
NETWORK	
Network Port	10/100M BASE-TX, RJ-45 Connector
Cabling Type	Category 6 and higher
Network Protocol	IPv4, HTTP, HTTPS, TCP/IP, Unicast/Multicast, UDP, RTP, RTSP, RTCP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, SNMP, UPNP, IEEE802.1X
ONVIF Protocol	ONVIF Compliant
Security	User Access with password protection, IP Filtering
Users	1 Administrator, 6 Users
Simultaneous Viewing	Up to 5 users
PC Web Browser	IE 6.0 Above; Mozilla Firefox; Google Chrome
Mobile Device	Windows Mobile, Symbian, iPhone, Android
Events	Motion, Tamper Detection, Sensor, Network Failure
Event Handlers	FTP, E-mail, Local Storage
MECHANICAL	
Housing ID	V4BOMWH670745A1
Dimensions (mm)	87 (W) x 242 (L) x 84 (H)
Weight (g)	650
Housing	Vandal Resistant Aluminum Alloy Housing
Finish	White Powder Coat, RAL 9003
Installation	Ceiling Mount / Wall Mount, 3-Axis Concealed Bracket
ELECTRICAL	
Power Consumption	440mA, 12V DC, 5.28 Watts
Power Source	PoE IEEE802.3af; DC12V
Power Connector	DC Male Plug
RTC Backup Battery	3V Magnesium Lithium
ENVIRONMENTAL	
Operating Temperature (C)	-20 to +60
Storage Temperature (C)	-20 to +60
Operating Humidity	0% - 95% non condensing
Ingress Protection Rating	IP67
Impact Rating	IKO7
STANDARDS COMPLIA	NCE
Emissions	FCC Part 15 Subpart B Class B EN 55022:2010 IC ICES-003 Class B
Immunity	EN 55024:2010

UL 609501, EU: 2001/95/EC GPSD

ORDERING INFORMATION		
PART NUMBER	DESCRIPTION	
INB713Z-RTN	Infinique Premium Series Outdoor IR Bullet Camera, 2MP, 2.8-12mm Motorized Zoom Lens, IR LED, 45m IR Range, H.265, H.264, MJPEG, Three Video Streams, D-WDR, True Day and Night with ICR, Adjustable Bit Rate, ONVIF Compliant, Two Way Audio, SDHC Slot, PoE, IP67	
IJBBWM-134	Infinique Wall Mount Junction Box, Base Diameter 134.3 mm	
IJBBCM-134	Infinique Ceiling Mount Junction Box, Base Diameter 134.3 mm	
IBKTCM	Infinique Pendant Mount Ceiling Bracket, 45 (D) x 294 (H) mm	
IBBCPM	Infinique Pole Mount Bracket with Metal Ties, 125 (L) x 46 (W) x 200 (H) mm	
IBCRWM	Infinique Corner Mount Bracket, 200 (L) x 130 (W) x 172.8 (D) mm	

Safety


## 2 Megapixel Premium Series IP IR Bullet Camera



## **Housing Accessories**













Infinique, a Canadian company is a manufacturer of high performing end-to-end solutions in copper, fiber and video surveillance systems. For more information visit our website at www.infinique.com or email us at sales@infinique.com.