

IND511Z-RWTN

5 Megapixel Premium Series IP WDR Dome Camera with IR

Infinique offers a wide range of IP based high definition cameras available in various housing formats, including Box, Dome and Bullet. Our cameras are equipped with superior image sensor and digital signal processor to produce sharp, crisp pictures and are enclosed in weather and vandal resistant housings making it suitable for use in all security applications. The ONVIF compliance of the cameras helps in easy integration, providing peace of mind for your investment. From small to very large installations, Infinique's cameras are reliable, future proof and an ideal solution for your video surveillance needs.

The IND511Z-RWTN is a 5 Megapixel 130dB WDR IR Dome Camera with Motorized Zoom. It is built with a sturdy plastic housing, incorporating a 1/2.8" high quality image sensor and IR LEDs to provide clear crisp images both during the Day and Night.


The camera comes equipped with a 2.8~8mm motorized zoom lens for easy setup of field of view. The auto iris control allows the camera to automatically set its iris position to maximize image quality in all lighting conditions. The camera streams real-time video at high definition resolution using H.264 or H.265 compression optimizing the bandwidth and increasing storage efficiency.

Built-in PoE for powering the camera and the flexible 3-axis bracket for fixing it on ceiling or wall, provides the convenience for installers to complete the installation quickly and with ease. These versatile cameras are suitable for video surveillance of government buildings, residential apartments, schools, colleges, universities, shopping malls, hospitals, hotels, industrial parks, and corporate offices.

Product Features

- 1/2.8" Progressive Sensor
- 5 Megapixel Resolution
- Up to 30fps at 2592 x 1944, 60fps at 1920 x 1080
- IR Distance up to 30 meters
- 2.8~8mm Motorized Zoom Lens with DC Auto Iris
- 130dB True WDR
- H.265 and H.264 Compressions
- Up to 3 Simultaneous Video Streams
- S/N Ratio of more than 50dB
- Micro SD Card Slot for Onboard Storage
- Two Wav Audio, Alarm I/O
- Power Over Ethernet (PoE), IEEE 802.3af
- **ABS Plastic Housing**
- Wall or Ceiling Mount with 3 Axis Bracket
- **ONVIF Compliant**





Accessories







Part No: IJBDWM-115 Wall Mount Junction Box

Part No: IJBDCM-115

Part No: IBDCFM-1 Ceiling Mount Junction Box Ceiling Flush Mount Bracket







Part No: IBDLWM-3 Indoor Wall Mount L Bracket

Part No: IBKTCM Pendant Ceiling Bracket

Part No: IBBCPM Pole Mount Bracket



Part No: IBCRWM Corner Mount Bracket

IND511Z-RWTN





IMAGE PERFORMANCE		
Image Sensor	1/2.8" Progressive Sensor	
Effective Pixels (H x V)	2592 (H) × 1944(V)	
Resolution (Megapixels)	5	
Minimum Illumination	0.002 lux (AGC ON) 0 lux with IR ON	
Image Rate (FPS)	30 @5MP, 60 @2MP	
S/N Ratio	More than 50dB	
IR Distance (m)	30	
LENS		
Focal Length (mm)	2.8~8 Motorized Zoom Lens	
Iris	DC Auto Iris	
Lens Mount	M14	
Aperture Ratio	F1.2	
Angle of View (deg)	H:105 (Wide)~46 (Tele), V:56 (Wide)~26 (Tele)	
VIDEO		
Video Compression	H.265 Main Profile H.264 Baseline Profile/Main Profile/High Profile	
Main Stream	2592 x 1944, 2592 x 1520, 2048 x 1536, 2304 x 1296, 1920 x 1080, 1280 x 960	
Sub Stream	1920 x 1080, 1280 x 720, 640 x 480	
Mobile Stream	640 x 480, 320 x 240	
Electronic Shutter Control	Auto, 1/8 ~ 1/20,000	
Day/Night Control	True Day/Night with IR Cut Filter	
Flicker Control	50 Hz, 60 Hz	
True WDR	130dB Variable Coefficient	
3D Noise Reduction	Auto / Manual / Disable	
White Balance	Automatic / Manual	
Back Light Compensation	On / Off	
Automatic Gain Control	Auto/Manual, Adjustable Level	
Privacy Mask Zones	Up to 4 Privacy Mask Zones	
Alarm IO	1x Input, 1x Output	
Audio Input/ Output	Line level input and output, 3.5mm A/V Interface	
Video Bit rate	256K-8M ,Supports CBR/VBR	
OSD	Camera ID, Timestamp	
Image Orientation	Image Flip, Corridor Mode, Rotation	
Image Controls	Brightness, Contrast, Hue, Saturation, Sharpness	
Advanced Functions	Image Rotation, Gain Control, Anti-Fog, Anti-False Color, Anti-Shake, IR Detection, Motion Detection	
VIDEO ANALYTICS		
Motion Detection	Multiple Zones	
Advance Video Analytics	Tamper, Out Of Focus, Sound, Perimeter Intrusion, Line Crossing, Stationary Object, Pedestrian Detection, People Counting, Face Detection	

LOCAL STORAGE	
	Minus CD Carel Many in to 05/OD
Storage Type	Micro SD Card, Max up to 256GB
Recording	Video and Image; Auto / Schedule/ Manual / On Event
NETWORK	
Network Port	10/100M BASE-TX, RJ-45 Connector
Cabling Type	Category 6 and higher
Network Protocol	IPv4, HTTP, HTTPS, TCP/IP, Unicast/Multicast, UDP, RTP, RTSP, RTCP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, SNMP, UPNP, IEEE802.1X
ONVIF Protocol	ONVIF Compliant
Security	User Access with password protection, IP Filtering
Users	1 Administrator, 6 Users
Simultaneous Viewing	Up to 5 users
PC Web Browser	IE 6.0 Above; Mozilla Firefox; Google Chrome
Mobile Device	iOS, Android
Events	Motion, Tamper Detection, Sensor, Network Failure
Event Handlers	FTP, E-mail, Local Storage
MECHANICAL	
Housing ID	V4DIPWH660730S2
Dimensions (mm)	120 (D) x 91.6 (H)
Weight (g)	390
Housing	ABS Plastic
Finish	White, RAL 9003
Installation	Ceiling Mount / Wall Mount, 3-Axis Bracket
ELECTRICAL	
Power Consumption	440mA, 12V DC, 5.28 W
Power Source	PoE IEEE802.3af; DC12V
Power Connector	DC Male Plug
RTC Backup Battery	3V Magnesium Lithium
ENVIRONMENTAL	
Operating Temperature (C)	-20 to +60
Storage Temperature (C)	-20 to +60
Operating Humidity	0% - 95% non condensing
Ingress Protection Rating	IP66
IK Rating	IK07
STANDARDS COMPLIA	NCE
Emissions	FCC Part 15 Subpart B Class B EN 55022:2010 IC ICES-003 Class B
Immunity	EN 55024:2010
Safety	UL 609501, EU: 2001/95/EC GPSD

ORDERING INFORMATION		
PART NUMBER	DESCRIPTION	
IND511Z-RWTN	Infinique Premium Series Indoor WDR IR Dome Camera, 5MP, 2.8-8mm Motorized Zoom Lens, IR Array LED, 30m IR Range, H.265, H.264, MJPEG, Three Video Streams, 130dB WDR, True Day and Night with ICR, Adjustable Bit Rate, SDHC Slot, ONVIF Compliant, PoE, IP66, IK07	
IJBDWM-115	Infinique Wall Mount Junction Box, Base Diameter 115 mm	
IJBDCM-115	Infinique Ceiling Mount Junction Box, Base Diameter 115 mm	
IBDCFM-1	Infinique Ceiling Flush Mount Bracket	
IBDLWM-3	Infinique Indoor Wall Mount L Bracket	
IBKTCM	Infinique Pendant Mount Ceiling Bracket, 45 (D) x 294 (H) mm	
IBBCPM	Infinique Pole Mount Bracket with Metal Ties, 125 (L) x 46 (W) x 200 (H) mm	
IBCRWM	Infinique Corner Mount Bracket, 200 (L) x 130 (W) x 172.8 (D) mm	

IND511Z-RWTN

5 Megapixel Premium Series IP WDR Dome Camera with IR



Housing Accessories


















Infinique, a Canadian company is a manufacturer of high performing end-to-end solutions in copper, fiber and video surveillance systems. For more information visit our website at www.infinique.com or email us at sales@infinique.com.