

PD1000 Series 2 Ports PoE Extender

Unmanaged Plug and Play 10/100/1000 Ethernet PoE Extender up to 200 Meters

Infinique's INPD1000 is an Ethernet PoE Extender that powers devices such as an IP Camera which are installed at distances which are greater than the Ethernet cabling standard of 100 meters. It has 2x RJ45 PoE output ports to provide Data and Power to connected devices while the 1x RJ45 port provides connectivity between the PoE Extender and the PSE such as a PoE switch.

This Ethernet PoE Extender is suitable for applications such as transportation, shipping, mining, energy, video surveillance, smart buildings, and any installation where IP devices are installed at distances of more than 100 meters.

Features and Benefits

Plug and Play Connectivity

Unmanaged Plug and Play PSE with 3x RJ45 Ethernet 10/100/1000Base-T Ports, 2x RJ45 Output Ports for Data and Power, 1x RJ45 Port for Input. No Additional Power Supply Required.

Excellent Performance

Switching capacity of 12 Gbps and forwarding speed of 4.46Mbps @64 bytes

Robust Design

IP30 ABS Plastic Flame Retardant PC Grade Enclosure, Fan-less Design, Excellent Heat Dissipation and provides Stable Operation

Port Lightning Protection

Port lightning protection common-mode 4KV, Differential mode 2KV

• Standards

Complies with IEEE 802.3af, 802.3at, 802.3u, 802.3x, 802.3ab, 802.1X, 802.1Q, 802.1P Standards



CONSTRUCTION

PD1000 Series 2 Ports PoE Extender

Unmanaged Plug and Play 10/100/1000 Ethernet PoE Extender up to 200 Meters

TECHNICAL SPECIFICATIONS

Ethernet RJ45 Ports	2x 10/100/1000 Base PoE Ports (Data/Power) auto-sensing, full/half duplex MDI/MDI-X self-adaption 1x 10/100/1000 Base-T(X) Uplink PD Port (Data/Power)
Network Protocols	IEEE 802.3,10BASE-T Ethernet, IEEE802.3i 10Base-T IEEE 802.3u, 100BASE-T Fast Ethernet Standard IEEE 802.3ab, 1000BASE-T Gigabit Ethernet Standard, IEEE802.3z 1000Base-X IEEE 802.3x, Full-Duplex Ethernet Data Link Layer Flow Control
Features	Half/Full-Duplex Operation at 10/100Mbps Full-Duplex Operation at 1000Mbps Auto-Negotiation for each port Auto MDI/MDIX
LED Indicator Status	Power: Green, Per Port Link/Act: Yellow, SFP: L/A Green
SWITCH PERFORMANCE	
Switching Bandwidth	12 Gbps
Forwarding Rate	4.46 Mpps @64byte
Network Delay	< 20 msec
Buffer Memory	2M
Jumbo Frame	9.2K
MAC Addresses Table Size	2К
MTBF	306,600 hours or 35 Years
POWER MANAGEMENT	
PoE Power Budget	25W, Max 25W Per Port, IEEE802.3af/at , Restricted by max input power of PSE
Power Supply Pin	Default: 1/2 (+), 3/6 (-), Optional 4/5(+), 7/8(-)
Power Consumption	Standby< 2W, Full load < 30W
Power Supply	Powered Device, RJ45 PoE port, No additional power supply required.
ENVIRONMENT	
Operating Temperature	-20°C to 55°C
Operating Relative Humidity	5% - 90%, non-condensing
Storage Temperature	-40°C to 80°C
Storage Relative Humidity	5% - 90%, non-condensing
Working, Storage Altitude	up to 10,000 ft / 3000 m
PHYSICAL CHARACTERISTICS	
Dimensions	50 (w) x 103 (d) x 29 (h) mm
Weight	0.07kg Net / 0.08kg Gross
Enclosure	IP30 ABS Plastic Fire Retardant PC Grade, Desktop or Wall mountable
STANDARDS COMPLIANCE	
Lightning protection / Protection level	Lightning Protection: 4KV 8/20us, Protection level: IP30
Mechanical Properties	IEC60068-2-6 (anti vibration) IEC60068-2-27 (anti shock) IEC60068-2-32 (free fall)
Certification	CCC; CE Mark, Commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS

ORDERING INFORMATION PART NUMBER DESCRIPTION Infinique INPD1000 Series 3 Ports PoE Extender, Distance 200 meters, 2x 10/100/1000 PoE Ports, 1x 10/100/1000 Uplink Port, Switching Capacity 12 Gbps, PoE Power Budget 25W, Max 25W Per Port, Plug and Play Configuration, IP30 ABS Plastic Fire INPD1000-2RP Retardant PC Grade Enclosure, Desktop or Wall Mountable



Infinique, a Canadian company is a manufacturer of high performing end-to-end solutions in copper, fiber and video surveillance systems. For more information visit our website at www.infinique.com or email us at sales@infinique.com.